



## Safety Data Sheet

Printed : 27/10/2025

Revised : CLP V1-R-1-CLP from 27/10/2025

### TOLU BAUME RESINOIDE

#### 1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY

##### 1.1. Product identifier

TOLU BAUME RESINOIDE

N° CAS : -  
N° CE : -  
N° index REACH An VI : /  
N° REACH (partially) : Exempt (mixture)

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of the substance/mixture** : Industrial use only

**End use** : **Fragrances / Cosmetic / Flavours**

##### 1.3. Details of the supplier of the safety data sheet

**Company** : PCW  
PARFUM COSMETIC WORLD  
45 Boulevard Marcel PAGNOL  
Parc Aromagrasse  
06130 GRASSE - FRANCE  
Tel: +33 (0)4 92 42 35 00  
Fax : +33 (0)4 92 42 35 19  
Web : www.pcwfrance.com  
Email : info@pcwfrance.com

**Technical manager** : regulatory@pcwfrance.com

##### 1.4. Emergency telephone number

###### Emergency information service of the company

+33(6) 07 85 74 60 (24h/24h)

###### National emergency information service

INERIS : +33(8) 20 20 18 16

###### Anti poison Centers in France

ORFILA : +33(1) 45 42 59 59

#### 2. HAZARDS IDENTIFICATION

# Safety Data Sheet

Printed : 27/10/2025

TOLU BAUME RESINOIDE

Revised : CLP V1-R-1-CLP from 27/10/2025

## 2.1. Classification of the substance or mixture

### GHS Classification :

(RegulationCLP)

Eye Dam. 1      Serious eye damage / eye irritation 1  
Aquatic Chronic 3      Hazardous to the aquatic environment, long-term hazard 3  
Skin Irrit. 2      Skin corrosion / irritation 2  
Skin Sens. 1      Sensitisation skin 1  
Stot Re 1      Specific target organ toxicity, repeated exposure 1

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H372 - Causes damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H412 - Harmful to aquatic life with long lasting effects.

## 2.2. Label elements

### GHS Classification :

(RegulationCLP)



Warning mention : Danger

Eye Dam. 1      Serious eye damage / eye irritation 1  
Aquatic Chronic 3      Hazardous to the aquatic environment, long-term hazard 3  
Skin Irrit. 2      Skin corrosion / irritation 2  
Skin Sens. 1      Sensitisation skin 1  
Stot Re 1      Specific target organ toxicity, repeated exposure 1

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H372 - Causes damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H412 - Harmful to aquatic life with long lasting effects.

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P301/303+P310 - If swallowed : Rinse mouth. Do not induce vomiting. Immediately call a poison center or doctor/physician.

# Safety Data Sheet

Printed : 27/10/2025

TOLU BAUME RESINOIDE

Revised : CLP V1-R-1-CLP from 27/10/2025

## 2.3. Other hazards

The substance/mixture does not contain components considered to have endocrine disrupting properties according to Article 57(f) of REACH or Commission Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0,1 % or more.

**Contains Cinnamic acid, Benzoic acid, Benzyl cinnamate, Cinnamal, Cinnamyl alcohol, Isoeugenol**

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

List of reportable components:

### 3.1. Substances

Numéro d'identification	Substance	Classes danger & Phrases H	LCS / Facteurs M / ATE	Percent %
CAS# 621-82-9 EINECS# 210-708-3	Cinnamic acid	Eye Irrit. 2, Stot Re 2 H319, H373		[ 20-50 ]
CAS# 65-85-0 EINECS# 200-618-2 REACH# N° INDEX 607-705-00-8	Benzoic acid	Eye Dam. 1, Skin Irrit. 2, Stot Re 1 H318, H315, H372		[ 10-20 ]
CAS# 120-51-4 EINECS# 204-402-9 REACH# N° INDEX 607-085-00-9	Benzyl benzoate	Acute Tox. 4 (Oral), Aquatic Acute 1, Aquatic Chronic 2 H302, H400, H411	ATE (Orale) : 1160mg/kg	[ 10-20 ]
CAS# 103-41-3 EINECS# 203-109-3 REACH# /	Benzyl cinnamate	Aquatic Acute 1, Aquatic Chronic 2, Skin Sens. 1B H400, H411, H317		[ 1-5 ]
CAS# 64-17-5 EINECS# 200-578-6 REACH# N° INDEX 603-002-00-5	Ethyl alcohol	Eye Irrit. 2, Flam. Liq. 2 H319, H225		[ 1-5 ]
CAS# 121-33-5 EINECS# 204-465-2 REACH# /	Vanillin	Eye Irrit. 2 H319		[ 1-5 ]
CAS# 104-55-2 EINECS# 203-213-9 REACH# /	Cinnamal	Eye Irrit. 2, Aquatic Chronic 3, Skin Irrit. 2, Skin Sens. 1A H319, H412, H315, H317		[ 0-1 ]
CAS# 104-54-1 EINECS# 203-212-3 REACH# /	Cinnamyl alcohol	Acute Tox. 4 (Oral), Skin Sens. 1B H302, H317	ATE (Orale) : 2000mg/kg	[ 0-1 ]
CAS# 97-54-1 EINECS# 202-590-7 REACH# /	Isoeugenol	Acute Tox. 4 (Dermal, Acute Tox. 4 (Inhala, Acute Tox. 4 (Oral), Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1A, Stot Se 3 H312, H332, H302, H319, H315, H317, H335	ATE (Dermale) : 1912mg/kg ATE (Orale) : 542mg/kg ATE (Inhalation) : 1.5mg/L	[ 0-1 ]

The substance/mixture does not contain components considered to have endocrine disrupting properties according to Article 57(f) of REACH or Commission Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0,1 % or more.

### 3.2. Mixtures

Not concerned

## 4. FIRST AID MEASURES

## Safety Data Sheet

Printed : 27/10/2025

TOLU BAUME RESINOIDE

Revised : CLP V1-R-1-CLP from 27/10/2025

### 4.1. Description of first aid measures

**General notes:** Please refer to the risk and safety statements (section 2)

**Following inhalation:** If inhaled : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Remove collar, belt, tie... Give artificial respiration if not breathing.

**Following ingestion:** If swallowed: Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Do NOT induce vomiting.

**Following skin contact:** If on skin (or hair) or clothing rinse immediately contaminated clothing and skin with plenty of water before removing clothes. If the symptom persists, consult a doctor.

**Following eye contact:** Rinse cautiously with water for several minutes (15 minutes open eyelids). Remove contact lenses, if present and easy to do. Continue rinsing. In case of disorder, consult an ophthalmologist.

**Self-protection of the first aider:** In lack of appropriate formation, none initiative should imply an individual risk.

### 4.2. Most important symptoms and effects, both acute and delayed

See section 2

### 4.3. Indication of any immediate medical attention and special treatment needed

**Contact with skin:** Wash immediately and abundantly with water and soap. Rinse then with clear water.

**Contact with eyes:** Abundant rinsing with water (15 minutes open eyelids) then washing with an ocular lotion standard Dacryoserum. In case of disorder, consult an ophthalmologist.

**In case of ingestion:** Do not induce vomiting, maintain the patient at rest. If problems persist, consult a doctor.

**Soiled clothing:** Withdraw soiled clothing and re-use them only after decontamination.

## 5. FIREFIGHTING MEASURES

### 5.1. Extinguishing media

**Suitable extinguishing media:** Use an extinguishing agent suitable for the surrounding fire. CO<sub>2</sub>, powder, foam, specific liquid. Do not inhale the fumes.

**Unsuitable extinguishing media:** Never use a direct stream of water.

### 5.2. Special hazards arising from the substance or mixture

**Flammability:** The product is not flammable.

**Prevention:** Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

#### **Hazardous combustion products:**

Release of poison gases: Monoxide de carbone (CO), Dioxyde de carbon (CO<sub>2</sub>), Oxyde d'azotes (NO<sub>x</sub>), Dioxyde de soufre (SO<sub>2</sub>), Cyanures (CN) ....

### 5.3. Advice for firefighters

**Never use a direct water jet.**

## Safety Data Sheet

Printed : 27/10/2025

TOLU BAUME RESINOIDE

Revised : CLP V1-R-1-CLP from 27/10/2025

### Special protective equipment for fire-fighters:

Firefighters should wear appropriate protective equipment and self-contained breathing apparatus with full face mask operating in active pressure mode.

## 6. ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Call immediately the emergency personnel.

Promote adequate ventilation in the area.

#### For non-emergency personnel

Keep them away from the area. Avoid all sources of ignition (spark of flame).  
Avoid skin/eye contact. Do not inhale vapours.

#### For emergency responders

Use personal protective equipment. In case of accidental spills, wear protective gloves during the handling.

### 6.2. Environmental precautions

Avoid the dispersion and flow of the product. Keep away from drains, surface and ground water.  
Inform the competent authorities if the product enters in ground or surface waters.

### 6.3. Methods and material for containment and cleaning up

#### For containment

The spillage is contained with sand or inert powder. The chemical waste is placed in sealed containers.

#### For cleaning up

The soiled elements (rags, absorbent papers, filters) are immediately soaked into water. The chemical waste are rapidly treated according to the local regulation.

#### Other informations

Only qualified personnel is allowed to clean up.

### 6.4. Reference to other sections

See section 8 for personal protective equipment and section 13 for waste treatment.

## 7. HANDLING AND STORAGE

### 7.1. Precautions for safe handling

#### Protective measures:

See section 2.2



## Safety Data Sheet

Printed : 27/10/2025

TOLU BAUME RESINOIDE

Revised : CLP V1-R-1-CLP from 27/10/2025

### Measures to prevent fire:

Do not smoke. Do not expose to excessive heat or ignition sources (spark or flame).

### Measures to prevent aerosol and dust generation:

Maintain adequate ventilation in the area.

### Measures to protect the environment:

Avoid spreading product and keep it from spilling. Precautions or coming in contact with the ground, waterways, drains and vents.

### Advice on general occupational hygiene:

Follow the general hygiene rules.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in its original packaging in a cool dry place, away from light.

**Technical measures:** Close the container after use.

In case of transferring, reproduce the labelling.

**Packaging materials:** Preserve only in the container of origin.

Respect the general rules of incompatibility.

Storage :

**Keep under Nitrogen, in fraiche temperature (max 18°C). Avoid prolonged exposure to light, humidity and air, in tightly sealed original container.**

### 7.3. Specific end use(s)

Wash hands and any other zone exposed with soap and water before eating, drinking, to smoke and before leaving work.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1. Control parameters

**Measures of technical order:** Avoid contact with eyes, skin and clothes. Do not ingest. Do not inhale vapors. Use proper personal protective equipment.

**Monitoring procedures:** If the product contains ingredients with exposure limits, it may be necessary to carry out a follow-up examination of people, the workplace atmosphere or living organisms to determine the effectiveness of ventilation or other control measures or to assess the need for respiratory protective equipment. It is important to refer to the European standard EN 689 on methods for assessing inhalation exposure to chemical agents and to national policy documents on methods for determining hazardous substances.

### 8.2. Exposure controls

#### Appropriate technical controls :

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure.

## Safety Data Sheet

Printed : 27/10/2025

TOLU BAUME RESINOIDE

Revised : CLP V1-R-1-CLP from 27/10/2025

### Personal protection measures :

#### Personal protection equipment :

- Hand protection: Protection not required.- Eye protection: Protection not required.- Respiratory protection: In case of insufficient ventilation, wear suitable respiratory equipment.

**Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates that is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Filter apparatus (dust masks or half masks)

#### Type of filters

Type AX (Brown) : Organic compounds boiling point < 65°C

Type A (Brown) : Organic compounds boiling point > 65°C

Type B (Grey) : Inorganic gasses and fumes.

Type P (White) : Particles, dusts and aerosols

**Hand protection** : Impermeable and chemical resistant gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary >8 hours before piercing : vinyle disposable.

**Remark** : The waterproofness of the recommended gloves does not only depend on their material. Also other factors can have an influence on the waterproofness, such as their thickness or specific use or temperature conditions. In any case, material certificates should be selected. Ask your supplier whether the gloves are suitable for this purpose.

**Eyes protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Recommended : Splash goggles, safety glasses with side-shields.

**Skin protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Body : Recommended : lab coat (sarrau), general.

Type 3 : Liquid impermeability

Type 4 : Aerosol impermeability

Type 6 : Impermeability limited to liquid splashes

Foot : Recommended : neoprene

Upper and sole resistant and impermeable (Hydrocarbure resistant).

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Solubility ethanol :	<b>Yes</b>
Appearance :	<b>Solid</b>
Colour :	<b>Light brown</b>
Odour :	<b>Characteristic</b>
Density 20/20°C :	-
Refractive index n (20/D) :	-
Optical rotation (°) :	-
Peroxides value mmol/kg :	-
Boiling point (°C) :	<b>&gt; 35</b>
Flash point (°C) (close cup) :	<b>&gt;= 100</b>

## Safety Data Sheet

Printed : 27/10/2025

TOLU BAUME RESINOIDE

Revised : CLP V1-R-1-CLP from 27/10/2025

### 9.2. Other information

Not concerned

## 10. STABILITY AND REACTIVITY

### 10.1. Reactivity

Avoid powerful oxidising agents

### 10.2. Chemical stability

Stable under normal conditions.

Shelf life : **18 months, according to storage conditions**

### 10.3. Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

### 10.4. Conditions to avoid

Avoid any potential source of heat.

### 10.5. Incompatible materials

**Incompatibility with other materials:**

### 10.6. Hazardous decomposition products

**Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

**Dangerous decomposition products:** No dangerous decomposition products known.

## 11. TOXICOLOGICAL INFORMATION

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Toxicological Informations Acute :**

· **Orale**

**DL50: 3033.407 (Defined)**

· **Inhalation**

**CL50: 0 (Estimated)**

· **Skin**

**No considered**

**further information:**

## Safety Data Sheet

Printed : 27/10/2025

TOLU BAUME RESINOIDE

Revised : CLP V1-R-1-CLP from 27/10/2025

### Cinnamic acid

ETAO : 3 570,00 mg/kg(Déterminée) ETAC : Non déterminée ETAI : Non déterminée

### Benzoic acid

ETAO : 2 565,00 mg/kg(Déterminée) ETAC : Non déterminée ETAI : Non déterminée

### Benzyl benzoate

ETAO : 1 160,00 mg/kg(Déterminée) ETAC : 0,00 mg/kg(Déterminée) ETAI : Non déterminée

### Benzyl cinnamate

ETAO : 3 280,00 mg/kg(Déterminée) ETAC : Non déterminée ETAI : Non déterminée

### Vanillin

ETAO : 3 300,00 mg/kg(Déterminée) ETAC : 2 600,00 mg/kg(Déterminée) ETAI : Non déterminée

### Cinnamal

ETAO : 2 220,00 mg/kg(Déterminée) ETAC : 0,00 mg/kg(Estimée) ETAI : Non déterminée

### Cinnamyl alcohol

ETAO : 2 000,00 mg/kg(Déterminée) ETAC : Non déterminée ETAI : Non déterminée

### Isoeugenol

ETAO : 542,00 mg/kg(Déterminée) ETAC : 1 912,00 mg/kg(Déterminée) ETAI : 1,50 mg/l(Déterminée)

LD50 oral (rat) : **3750.01 mg/kg**LD50 Dermal (rabbit) : **No data**

### 11.2. Information on other hazards

The product does not contain substances identified as having endocrine disrupting properties (human health) in concentrations equal to or greater than 0.1% (m/m).

## 12. ECOLOGICAL INFORMATION

### 12.1. Toxicity

Do not leave the product, even diluted or in great quantity, penetrate the ground water, water or the drains.

### 12.2. Persistence and degradability

Not concerned

### 12.3. Bioaccumulative potential

Not concerned

### 12.4. Mobility in soil



## Safety Data Sheet

Printed : 27/10/2025

TOLU BAUME RESINOIDE

Revised : CLP V1-R-1-CLP from 27/10/2025

**PNEC soil** :

### 12.5. Results of PBT and vPvB assessment

**vPvB** :  
**PBT** :

### 12.6. Endocrine disrupting properties

The product does not contain substances identified as having endocrine disrupting properties (environment) in concentrations equal to or greater than 0.1% (m/m).

### 12.7. Other adverse effects

Not concerned

## 13. DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Product:** Recommendation: Does not have to be evacuated with the refuse. Do not let penetrate into drains/waste water system.

**Not cleaned packing:** Recommendation: Evacuation in accordance with the regulations.

## 14. TRANSPORT INFORMATION

### 14.1. UN number or ID number

ADR/ADN/RID : NR  
IMDG:NR  
IATA :NR

### 14.2. UN proper shipping name

ADR/ADN/RID : Not regulated for transport  
IMDG:Not regulated for transport  
IATA :Not regulated for transport

### 14.3. Transport hazard class(es)

ADR/ADN/RID : Not concerned  
IMDG:Not concerned  
IATA :Not concerned

### 14.4. Packing group

ADR/ADN/RID : Not concerned  
IMDG:Not concerned  
IATA :Not concerned

### 14.5. Environmental hazards

## Safety Data Sheet

Printed : 27/10/2025

TOLU BAUME RESINOIDE

Revised : CLP V1-R-1-CLP from 27/10/2025

IMDG :

### 14.6. Special precautions for user

Not concerned

### 14.7. Maritime transport in bulk according to IMO instruments

(Except particular case)

#### IBC Liquid substances

Metal (31A, 31B, 31N)

Plastic (31H1, 31H2)

#### GRV Solid substances

Metal (11A, 11B, 21A, 21N)

Plastic (11H1, 11H2, 21H1, 21H2)

## 15. REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Custom tariff :

**3302 10 21 00**

### 15.2. Chemical safety assessment

Not concerned

## 16. OTHER INFORMATION

### Full H sentences text in point 3

**H225** Highly flammable liquid and vapour

**H302** Harmful if swallowed.

**H302+H312** Harmful if swallowed or in contact with skin

**H302+H312+H332** Harmful if swallowed, in contact with skin or if inhaled

**H302+H332** Harmful if swallowed or if inhaled

**H315** Causes skin irritation.

**H317** May cause an allergic skin reaction.

**H318** Causes serious eye damage.

**H319** Causes serious eye irritation.

**H335** May cause respiratory irritation.

**H372** Causes damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

**H373** May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

## Safety Data Sheet

Printed : 27/10/2025

TOLU BAUME RESINOIDE

Revised : CLP V1-R-1-CLP from 27/10/2025

**H400** Very toxic to aquatic life.

**H411** Toxic to aquatic life with long lasting effects.

**H412** Harmful to aquatic life with long lasting effects.

Material security data sheet according to 2020/878/CEE.

These indications are founded on the current state of our knowledge, but do not constitute a guarantee as for the properties of the product and do not give place to a contractual legal report.